

VORLANE[®] | SINCE 2007

Leading Led Lighting Manufacturer

Your Closely Business Partner / Save Your Time & Cost

VORLANE[®]

Reflective Cup

30/60/90/120/150/180W LED Solar Street Light

Power	Size(mm)	LED Chip	Battery Capacity	Solar Panel(mm)
30 Watt	285 x 188 x 55	40 Pcs	3.2V 4AH	6V,4W/246x171
60 Watt	378 x 188 x 55	80 Pcs	3.2V 5AH	6V,6W/336x171
90 Watt	495 x 188 x 55	120 Pcs	3.2V 6AH	6V,8W/457x171
120 Watt	586 x 188 x 55	160 Pcs	3.2V 8AH	6V,10W/547x171
150 Watt	700 x 188 x 55	200 Pcs	3.2V 10AH	6V,12W/638x171
180 Watt	790 x 188 x 55	240 Pcs	3.2V 12AH	6V,15W/746x171

Charging Time: 5-8Hours Discharging Time : 8-24Hours

Waterproof Level : IP65 Input Voltage : AC85-285V 50-60HZ



Tian Wen

200/250/300W LED Solar Street Light

Power	Size(mm)	LED Chip	Battery Capacity	Solar Panel(mm)
200 Watt	620 x 280 x 56	384 Pcs	3.2V 10AH	5V,13W/518x200
250 Watt	690 x 280 x 56	480 Pcs	3.2V 15AH	5V,16W/580x200
300 Watt	760 x 280 x 56	576 Pcs	3.2V 20AH	5V,20W/650x200

Charging Time: 5-6Hours **Discharging Time :** 60-70Hours

CCT : 2700-6500K **Waterproof Level :** IP65

Input Voltage : AC85-285V 50-60HZ



Integrated

200/300/400W LED Solar Street Light

Power	Size(mm)	LED Chip	Battery Capacity	Solar Panel(mm)
200 Watt	447 x 342 x 70	480 Pcs	3.2V 12AH	6V,15W/335x360
300 Watt	597 x 342 x 70	640 Pcs	3.2V 20AH	6V,25W/335x510
400 Watt	677 x 342 x 70	1600 Pcs	3.2V 25AH	6V,30W/335x590

Charging Time: 5-8Hours **Discharging Time :** 8-24Hours

CCT : 2700-6500K **Waterproof Level :** IP65

Input Voltage : AC85-285V 50-60HZ



Integrated

50/100/150/200W LED Solar Street Light

Power	Size(mm)	LED Chip	Battery Capacity	Solar Panel(mm)
50 Watt	500 x 220 x 43	99 Pcs	3.2V 10AH	6V,15W
100 Watt	700 x 220 x 43	198 Pcs	3.2V 15AH	6V,20W
150 Watt	900 x 220 x 43	297 Pcs	3.2V 20AH	6V,25W
200 Watt	1000 x 220 x 43	396 Pcs	3.2V 25AH	6V,30W

Charging Time: 5-8Hours **Discharging Time :** 8-24Hours

CCT : 2700-6500K **Waterproof Level :** IP65

Input Voltage : AC85-285V 50-60HZ



Buffalo

200/250/300W LED Solar Street Light

Power	Size(mm)	LED Chip	Battery Capacity	Solar Panel(mm)
200 Watt	1618 x 538 x 98	120 Pcs	12.8V 30AH	18V,150W
250 Watt	1618 x 538 x 98	180 Pcs	12.8V 42AH	18V,150W
300 Watt	1618 x 695 x 98	240 Pcs	12.8V 60AH	18V,200W

Charging Time: 4-6Hours **Discharging Time :** 12-24Hours

CCT : 6500K **Waterproof Level :** IP65

Input Voltage : AC85-285V 50-60HZ



Interstellar One

100/200/300/400W LED Solar Street Light

Power	Size(mm)	LED Chip	Battery Capacity	Solar Panel(mm)
100 Watt	520 x 260 x 80	192 Pcs	3.2V 18AH	5V,25W/430x350
200 Watt	520 x 260 x 80	192 Pcs	3.2V 30AH	5V,35W/580x350
300 Watt	600 x 300 x 80	300 Pcs	3.2V 36AH	5V,40W/630x350
400 Watt	600 x 300 x 80	300 Pcs	3.2V 48AH	5V,50W/670x445

Charging Time: 5-8Hours **Discharging Time :** 48Hours

CCT : 6000-6500K **Waterproof Level :** IP65

Input Voltage : AC85-285V 50-60HZ



VORLANE® / SINCE 2007

Professional Passionate Persistence

Contact us now to discover more about our products and get a customized solution!

**CEO and Founder of Vorlane:
Steven Liang**

☎ +86 189 2538 9688

☎ +86 139 2536 6726

🌐 www.vorlane.com

✉ steven@vorlane.com

Office in
China :

Guangzhou Vorlane Optoelectronics Technology Co., Ltd
Leshan Street, Gexin Road, Haizhu District, Guangzhou, 510220, China.

Office in
Brazil :

Mr Ltda
Rua do Gasômetro, 597 - Brás, São Paulo - SP, 03004-001

Factory in
China:

Zhongshan Wolink Lighting CO., LTD.
Wolink Lighting Bld, Caosan Zone, Guzhen, Zhongshan, 528410, China.



Wechat



Whatsapp



Company Details